

EXECUTIVE SUMMARY

Fusion Reactor LinealFRC6T Gatling (CERN-DOI-REGISTERED)

© <https://openfusionfoundation.org>

2026

Contents

EXECUTIVE SUMMARY: Resilient Industrial Fusion Plant (RIF) and LinearFRC6T Gatling Architecture (30+10)	1
1. Introduction: The Collapse of the Traditional Paradigm and the RIF Path	2
2. Core Innovation: The LinearFRC6T Tube (The Work Unit)	2
3. Plant Architecture: Gatling 30+10 Topology (The Joint System)	3
4. Thermodynamic Ecosystem and Hybrid Extraction	4
5. Economic Viability and Supply Chain	5
6. The Plasma's Journey: Chronology of a Shot at Mach 7.8	5
7. Final Conclusion: The Deployment Horizon	7

EXECUTIVE SUMMARY: Resilient Industrial Fusion Plant (RIF) and LinearFRC6T Gatling Architecture (30+10)

- **Project:** Fusion Plant "RIF-v101" (*Resilient Industrial Fusion*)
- **Architecture:** LinearFRC6T-Gatling(30+10)-Hybrid Fusion Reactor
- **Author:** (c) Leopoldo Cano Guardiola - leo@ulogicmind.ai - (DOI-Registered) <https://doi.org/10.5281/zenodo.22070202>
- **Foundation:** <https://openfusionfoundation.org>
- **Document Version:** v101
- **Open License:** CERN OHL-S (Strongly Reciprocal)

§ 1. Introduction: The Collapse of the Traditional Paradigm and the RIF Path

The traditional nuclear fusion paradigm has failed on the assembly line. For over half a century, the industry has tried to build a star in a bottle by confining unstable plasmas inside complex toroidal cages. This quest for infinite static confinement has led us to a thermodynamic and metallurgical dead end. It demands non-existent materials and unaffordable budgets.

The RIF (*Resilient Industrial Fusion*) project is born to break out of this stagnation. Instead of forcing the laws of physics to achieve a static plasma, we redesign the machine to process it in motion. The RIF Plant is the first commercial fusion architectural design capable of delivering up to **271 MWe** net of continuous baseload power adapted to demand. It achieves this using off-the-shelf industrial parts (COTS technology), removable modules, and a linear accelerator design. It is a power plant conceived to be built and made profitable in the current decade, leaving behind dependence on extreme physics.

§ 2. Core Innovation: The LinearFRC6T Tube (The Work Unit)

Instead of enclosing the fire in a spherical chamber and forcing metals to their melting point, we let the plasma fly along an immense straight tube. This dilutes the thermal punishment on the walls and facilitates the evacuation of atomic ashes.

We adopt a kinematic flight model. The thermonuclear projectile (Field-Reversed Configuration or FRC) travels at **2666 m/s**. This speed guarantees a transit window of **30 ms**. The plasma travels down a straight **80-meter** barrel confined by a uniform magnetic field of **6.0 T**. For this ecosystem to work in the real world without the plasma collapsing, we resolve four fundamental bottlenecks:

- **The Challenge of ballistic stability ($m=1$ and $n=2$ modes):** Classical physics dictates that a plasma flying 80 meters will flip on its axis ($m=1$ mode) or spin until it tears itself apart via centrifugal force ($n=2$ mode) in fractions of a millisecond. **Our Countermeasure (Empirical kinematic anchoring):** We apply the stabilization strategies empirically demonstrated by laboratories like TAE Technologies. We inject Neutral Beams (NBI) into the static chamber before firing. This forges a population of fast ions with long orbits that act as an internal gyroscope, preventing transverse flipping. Simultaneously, tungsten electrodes inject voltage into the external magnetic lines (*Edge Biasing*). This electric shearing brakes the destructive rotation. Finally, if the projectile suffers a transverse drift, a passive shield intervenes. Independent Tungsten-Rhenium (**W-Re**) tiles operate embedded in the chassis channels. As the plasma approaches, it induces local eddy currents in these tiles, unleashing a repulsive Lenz force that returns the projectile to its strict flight axis.
- **The Challenge of thermal confinement during flight:** Maintaining geometric shape is useless if heat dissipates via turbulence before completing the **30 ms** journey. **Our Countermeasure (Gyro-Bohm Scaling):** The architecture assumes the empirical scaling laws of the FRC. By operating with a massive core radius of **0.493 m** under a strict separatrix parameter of **$x_s = 0.58$** and a high-density

magnetic field of **6.0 T**, thermal leakage (Gyro-Bohm transport) plummets. These dimensions guarantee that the energy confinement time far exceeds the ballistic flight duration. The projectile crosses the chamber preserving its **15 keV** of ignition intact.

- **The Challenge of atomic damage:** The continuous flux of **14.1 MeV** neutrons destroys any wall exposed at a fixed point. **Our Countermeasure (Geometric dilution):** By stretching the reactor to **80 meters**, we spread the thermal punishment over an immense surface area of **427 m²**. This drops the wall thermal load to a trivial **50 kW/m²** (compared to the **10 MW/m²** of a Tokamak). We abate the displacements per atom (DPA) damage. This allows us to use proven nuclear-grade steels (like Eurofer-97) and discard experimental laboratory compounds.
- **The Challenge of vacuum asphyxiation:** After every fusion heartbeat, the tube is left full of residual ashes. If we don't clear the barrel, the next projectile hits a wall of gas and collapses. **Our Countermeasure (Ballistic Transport and Massive Suction):** To recover an ultra-high vacuum of **10⁻⁸ Torr** in an immense volume of **602 m³** in barely **7.5 s**, the plant requires colossal suction. Instead of installing fragile rotors in the hot zone, the plasma acts as a piston (Mass Ballistic Transport), dragging the ashes toward terminal vaults outside the walls. There, a **50 m²** surface of getter chemical alloy (NEG Zr-V-Fe) at 200 °C devours the reactive isotopes at an extreme rate of **1,000,000 L/s** by pure contact. Complementarily, perimeter MagLev turbopumps extract the remaining inert Helium ashes.

The Physical Architecture (9-Phase Coupling): To house these mitigations, the travel does not occur in a uniform cylinder. The machine is divided into 9 continuous physical phases. These stages couple their diameters and magnetic fields to guide expansion without supersonic shocks:

1. **Generation and Transition (Phases 1 to 3):** The plasma is born at a diameter of **1.20 m** under a magnetic compression of **7.2 T**. After assimilating the gyroscopic anchoring, it takes a blind curve to protect the injection equipment from radiation. It then widens isentropically to **1.70 m** while the field drops to **6.0 T** to achieve turbulence-free ignition.
2. **Combustion Flight (Phase 4):** The projectile crosses the main **80-meter** barrel, maintaining the strict **1.70 m** diameter confined by the **6.0 T** magnetic rail.
3. **Extraction and Sink (Phases 5 to 9):** The conduit diverges aerodynamically to **3.00 m**. The magnetic field is forcibly dropped to **0.75 T**, ending at **0 T**. Upon expanding, the plasma delivers direct electricity, smashes its shrapnel against passive blind walls, and dissipates its sonic pressure to be suctioned.

§ 3. Plant Architecture: Gatling 30+10 Topology (The Joint System)

The plant functions like a multi-cylinder industrial engine. We avoid building a single giant reactor that could paralyze the plant due to a local breakdown. To ensure a commercial electrical flow, we resolve two major structural limits:

- **The Challenge of intermittent supply:** Each tube demands a **7.5 s** pause to evacuate its gases. A single tube would deliver unacceptable pulses to the power grid. **Our Countermeasure (Gatling sequential firing):** We divide the load into 40 independent tubes arranged in a herringbone pattern at **45°**. While one tube is cleaning, the system fires the others in a synchronized sequence. We transform isolated explosions into a continuous heat flow. This redundancy allows us diurnal arbitrage: we operate **20** tubes during off-peak hours (using the pause to thermally regenerate the UHV vacuum chemical walls of the inactive tubes) and throttle up to **35** active tubes to maximize billing during peak hours.
 - **The Challenge of nuclear degradation:** Atomic bombardment degrades materials over the long term, condemning traditional reactors to costly decommissionings. **Our Countermeasure (Standardized modularity):** We build the plant from interchangeable COTS parts. We fragment the immense combustion chamber into **15-meter** cartridges assembled via hydraulic tension. If a component fatigues, a robotic crane simply removes the damaged module diagonally and slots in a replacement. We execute this hot swap without stopping the generation of adjacent tubes.
-

§ 4. Thermodynamic Ecosystem and Hybrid Extraction

We extract energy from the plasma and process it outside the walls. We always protect the civil grid from any radioactive event through realistic thermodynamics.

- **The Challenge of the D-T balance and Tritium scarcity:** In Deuterium-Tritium fusion, 80% of the energy escapes as **14.1 MeV** fast neutrons that ignore the magnets. Extracting energy solely via electromagnetic conversion is insufficient. Furthermore, Tritium is extremely scarce, and without self-generation, the plant is unviable. **Our Countermeasure (Hybrid extraction and in-situ breeding):** We harvest the megawatts through a dual approach. First, a surrounding blanket of molten salt (**FLiBe**) absorbs the entire neutron flux. To avoid magnetohydrodynamic (MHD) blocking, we inject the salt at an asymptotic grazing angle of **8°** so that it flows strictly parallel to the **6.0 T** magnetic lines. Driving a colossal master flow of **3920.59 kg/s**, this blanket delivers stabilized heat at **600 °C** and breeds Tritium in situ, ensuring a Tritium Breeding Ratio (TBR) greater than **1.05** to guarantee atomic self-supply. We continuously extract the fuel via micro-bubble drag (*Helium Sparging*). Second, we apply inductive braking (Direct Conversion) at the end of the tube to catch 20% of the remaining kinetic energy, generating backup electricity.
- **The Challenge of the cryogenic inferno:** Operating magnets at **4 K** just centimeters away from a **600 °C** core threatens to boil the liquid Helium and unleash a magnetic collapse (*quench*). **Our Countermeasure (AMMLI Shielding and Bronze-Aluminum):** We protect the magnetic chassis by installing a stepped all-metal thermal shield (AMMLI) that rejects radiant heat. We wrap the chamber in Bronze-Aluminum jackets to absorb cross-eddy currents (magnetic crosstalk at **4 Hz**), shielding the cryogenics.

To transform the heat into continuous commercial power, we deploy an isolated civil ecosystem:

- **Helium Firewall:** We use inert Helium gas at **100 bar** passing through bulk aluminized heat exchangers (*Pack-Cementation*). This intermetallic alumina phase physically blocks any isotopic Tritium leak toward the commercial turbines.
 - **Thermal Battery (TES):** Passive pools with **17,450 tons** of chloride salts flatten the nuclear heartbeats. If the national grid collapses (*Load Rejection*), these pools absorb the thermal excess without bursting the boiler making.
 - **Net Generation:** Assuming a realistic fusion gain factor in the plasma ($Q \approx 6.4$), the heat powers turbines driven by Supercritical Carbon Dioxide (**sCO₂**) at **150 bar**, raising the isentropic efficiency to **46.2%**. Because the colossal electrical consumption of the radiofrequency injection is self-supplied via Direct Energy Conversion (DEC), isolating itself from the grid, the thermal turbine only deducts the cryogenic and vacuum tolls, delivering up to **271 pure, marketable net MWe** to the public grid.
-

§ 5. Economic Viability and Supply Chain

The RIF design crushes traditional astronomical costs. It wagers exclusively on standard parts that the petrochemical and aerospace industries already mass-produce.

By isolating technological risk and avoiding impossible laboratory components, we turn fusion into a modular manufacturing process. Validated financial data project the following margins:

- **Capital Risk Reduction (CAPEX):** For mature commercial plants built in series, the initial investment compresses to a range of **2950 to 4100 USD/kWe**.
- **Operational Competitiveness (LCOE):** The Levelized Cost of Energy stabilizes between **45 and 60 USD/MWh**.

These metrics smash the economic barrier of large fission reactors. Our design demonstrates that fusion energy can compete financially head-to-head with combined-cycle natural gas and attract fully private capital.

§ 6. The Plasma's Journey: Chronology of a Shot at Mach 7.8

To understand the plant's thermodynamic integration, we must follow the ballistic path of a single thermonuclear projectile. The entire cycle of forging, combustion, and extinction occurs along a developed ballistic trajectory of **218.88 meters** (folded into a net footprint of 185 meters) in barely **110 milliseconds**.

The machine acts as an accelerator segmented into five major operational stages that adapt the magnetic field to the plasma's state:

Stage 1: Birth and Acceleration (Phase 1)

- **The Challenge:** Arm the projectile and accelerate it without exposing the injectors to direct neutron damage.
- **Our Countermeasure:** The plasma is born in a **60-meter** diagonal chamber. In its first resting moments, neutral beams (NBI) imprint a fast ion shell to stabilize it without suffering aerodynamic friction. Immediately after, a peristaltic magnetic wave squeezes and accelerates it to **2666 m/s**. The projectile reaches an initial **12 keV** protected by an optical shield against the central reactor.

Stage 2: Blind Transit and Ignition (Phases 2 and 3)

- **The Challenge:** Guide the plasma to the main barrel and raise it to fusion temperature without injecting neutral mass that brakes its flight.
- **Our Countermeasure:** The projectile takes a magnetic curve equipped with a quadrupole. This inflection acts as a firewall: the destructive retreating radiation crashes in a straight line into a blind Tungsten wall. After the curve, the tube widens passively. A radiofrequency system injects **3.2 GW** of clean energy. The plasma absorbs the wave and reaches the final **15 keV** of ignition upon entering the hot zone.

Stage 3: Ballistic Combustion (Phase 4)

- **The Challenge:** Confine the nuclear fire during its journey without it grazing the ceramics or suffering flipping.
- **Our Countermeasure:** The burning ring travels down the **80-meter** straight barrel enveloped by an immovable **6.0 T** field. It travels floating on a **35 cm** vacuum cushion. Any plasma oscillation induces automatic repulsive electromagnetic forces in the wall tiles, returning it to the center. For **30 ms**, it unleashes the neutron hurricane that heats the outer liquid salt to **600 °C**.

Stage 4: Electromagnetic Harvest and Filtering (Phases 5 and 6)

- **The Challenge:** Extract excess kinetic energy and separate the charged flow from the atomic shrapnel.
- **Our Countermeasure:** The conduit diverges and the field drops forcedly to **0.75 T**. As it widens, the plasma pushes against an outer dielectric copper cage. By Lenz's Law, this interaction generates electricity and brakes the projectile to **1686 m/s**. Next, the flow takes a second diversion curve: the neutral debris continues straight until it destroys itself against an inclined passive block, while the ionized gas obeys the magnets and turns cleanly.

Stage 5: Deactivation and Recycling (Phases 7, 8 and 9)

- **The Challenge:** Extinguish the plasma before the magnetic field disappears at **0 T** to prevent its volumetric explosion against the boilermaking.

- **Our Countermeasure:** In the final stretch, we inject a strict curtain of cold Helium. The plasma collides, loses its electrical charge, and transitions to neutral gas. It expands harmlessly through an immense paramagnetic vault, dissipating its pressure wave to **0.62 bar**. Immediately, perimeter MagLev turbopumps extract the ashes, purify the fuel via Palladium membranes at **400 °C**, and restore the ultra-high vacuum in exactly **7.5 s**, leaving the tube pristine for the next Gatling heartbeat.
-

§ 7. Final Conclusion: The Deployment Horizon

The RIF Plant represents a tangible leap toward the industrialization of fusion energy. Instead of pushing the limits of theoretical physics, we have integrated thermodynamics, materials science, and commercial viability into a strictly coupled model.

The linear architecture turns challenges into solutions via its 9 continuous phases. As the tube alters its inner diameter (from the **1.20 m** of injection, through **1.70 m** of the primary barrel, until expanding to **3.00 m** at extraction), the magnetic field is modulated in strict synchrony (scaling from **7.2 T** to **6.0 T**, to finally decay to **0.75 T**). This aerodynamic transition prevents structural collisions.

This rigor guarantees the system's kinematic equilibrium. There is an unalterable harmony between the safe flight time (**30 ms**), the massive barrel length (**80 m**), and the demanded cruising speed (**2666 m/s**). Dynamic mechanisms (NBI and *Edge Biasing*) provide active anchoring, while passive Tungsten-Rhenium tiles exert immediate repulsive forces against any drift. The plasma is stabilized just long enough to deliver its thermal load.

The immense FLiBe primary blanket absorbs the colossal atomic shock and breeds Tritium, while chloride batteries flatten the heartbeats to drive commercial sCO₂ turbines with high efficiency. By assembling these validations exclusively using COTS technology, the plant advances firmly toward its sub-scale hardware validation.

The commercial mastery of fusion no longer demands taming a star, but building the industrial engine capable of processing it.